



AUSTRALIAN
BAKERY AND PIZZA

QUALITY BAKERY
PIZZA EQUIPMENT

CFI Retarder Prover - Hand Load for Trays

AFB & AFJ - hand load for trays

Products from the AFJ range are retarder prover cabinets, reduced to height with regard to the AFB range, both are designed to receive trays, grids or meshes of size 400x600, 460x800, 400x800 and 600x800.

The range consists of several standard single compartment, 1-door models :

- 1 model AFJ46 : tray size 400 x 600 - C TOUCH Control Panel
- 1 model AFJ48 : tray size 400 x 800 - C TOUCH Control Panel
- 1 model AFB468 : tray size 460 x 800 - C TOUCH Control Panel

A construction of quality, respectful of the environment.

- In the standard version, each model is delivered fitted with a humidity generator, with a very efficient electronic probe.
- The 60mm-thick panels are injected to a density of 45kg/m³ by a high pressure injection machine (135 bar)
- The combination of the thickness and density of the rigid polyurethane foam insulating material has been specially designed according to operational requirements, thereby minimizing heat loss and energy consumption.
- Panel surfaces in 6/10ths galvanized steel covered with a food quality PVC film of 120 micron
- All interior angles are rounded
- All interior fittings in 100% food quality 404 stainless steel
- Double glazed glass window



All the inner angles are rounded for easy cleaning and better hygiene. Sloping angle compliant with N.F.H.A standards.

All materials used for the interior layout are in 404 stainless steel.



50 - 52 NORCAL ROAD, NUNAWADING, VICTORIA. 3131
 ☎ +61 3 9878 6900 🖨 +61 3 9878 6966 ✉ sales@abpatlas.com.au



AUSTRALIAN
BAKERY AND PIZZA

QUALITY BAKERY
PIZZA EQUIPMENT



C-Touch
Control
Panel



AFJ 46	TRAYS 400 x 600 HAND LOAD 1 Door Cabinet C TOUCH control panel			
	AFJ 46 Retarder Proofer Cabinet 400 x 600 - 20 levels			
	Size of Trays	400 x 600	No. of levels	20
	No. of supports per level	1	Total no. of support	20
	Spacing out of levels	63 mm	Adjustable every	21 mm
	Tray entry direction	400	Level depth	600
	Refrigerating unit	1 refrigerating unit of 1/4 CV	No. of doors	1
	Refrigerating capacity at -10°C	0,45 KW	Fluid	R404A
	Voltage	240V ~1PH+N+T	Frequency	50 HZ
	Connecting electrical power	0,9 KW	Connection	5 A

AFJ 48	Trays 400 x 800 HAND LOAD 1 Door Cabinet C TOUCH control panel			
	AFJ 48 Retarder Proofer CABINET 400 x 800 - 20 levels			
	Size of Trays	400 x 800	No. of levels	20
	No. of supports per level	1	Total no. of support	20
	Spacing out of levels	63 mm	Adjustable every	21 mm
	Tray entry direction	400	Level depth	800
	Refrigerating unit	1 refrigerating unit of 3/8 CV	No. of doors	1
	Refrigerating capacity at -10°C	0,74 KW	Fluid	R404A
	Voltage	240V ~1PH+N+T	Frequency	50 HZ
	Connecting electrical power	0,9 KW	Connection	5 A

AFB 468	Trays 460 x 800 HAND LOAD 1 Door Cabinet - C TOUCH Control panel			
	AFB 468 Retarder Proofer CABINET 460 x 800 - 24 levels			
	Size of Trays	460 x 800	No. of levels	24
	No. of supports per level	1	Total no. of support	24
	Spacing out of levels	63 mm	Adjustable every	21 mm
	Tray entry direction	460	Level depth	800
	Refrigerating unit	1 refrigerating unit of 3/8 CV	No. of doors	1
	Refrigerating capacity at -10°C	0,6 KW	Fluid	R404A
	Voltage	240V ~1PH+N+T	Frequency	50 HZ
	Connecting electrical power	0,9 KW	Connection	5 A



50 - 52 NORCAL ROAD, NUNAWADING, VICTORIA. 3131
 +61 3 9878 6900 +61 3 9878 6966 sales@abpatlas.com.au